

LED

bullauge 6 SYSTEMLEUCHTE bu6-800-G5

Die Wand-, Decken- und Pendelleuchte bu6 (LED) ist jetzt in der fünften Generation erhältlich. Durch die opake Plexiglasscheibe und die gleichmäßige Anordnung der LEDs entsteht eine diffuse und sehr homogene Leuchtfläche. Dank mawa-Verschluss ist eine Ein-Mann-Revision unkompliziert durchführbar. Die Pendelvarianten der bu6 mit einem Durchmesser von 800 mm haben serienmäßig eine 3-fach-Parallelabhängung inkl. einem Anschlussbaldachin (ø76 mm).



weiß matt (RAL 9016)





weitere RAL-Farben auf Anfrage




bu6-800-G5-...-wm

bu6-800-G5-...-wa
bu6-800-G5-...-wa-u


bu6-800-G5-...-p
bu6-800-G5-...-p-u



800



800



800

(* Standardmaß)

bu6-800-G5

Design: Martin Wallroth

Engineering: mawa design

Wand-, Wandabstands-, Decken- und Pendelleuchte, Aluminiumgehäuse pulverbesch., satinierendes Plexiglas 5 mm,

LED Modul standard G5:

Downlight: 157 W, Ra > 90 (typ. 92)

Lichtfarben / Lichtstrom: 2700 K / 21000 lm,
3000 K / 22070 lm,

Uplight: 24 W, Ra > 90 (typ. 92)

Lichtfarben / Lichtstrom: 2700 K / 2960 lm,
3000 K / 3104 lm,

Lebensdauer Standard-LED:

L80 > 54.000 h (IES LM-80 / TM-21)

bu6-800-G5-4 DALI dimmbar

bu6-800-G5-7 Phasen- und -abschnitt dim.

Montagemöglichkeiten:

Wand- und Deckenmontage (-wm),

Wandanschlussplatte (-wa) mit 3 Distanzen,
optional mit Uplight (-wa-u) Standardlänge
50 mm (andere Längen auf Anfrage)

Pendelabhängung (-p) inkl. Baldachin,
3-fach-Parallelabhängung und Zuleitung
optional mit Uplight (-p-u)

Gewicht: bu6-800-wm 12 kg,

bu6-800-wa 12,5 kg, bu6-800-p 12 kg

LED

bullauge 6 SYSTEM LIGHT bu6-800-G5

The wall, ceiling, and pendant light, bu6 (LED) is now available in its 5th generation. The opaque plexiglass pane and even arrangement of LEDs creates a diffused and very homogenous lighting surface. Thanks to the mawa-closure, maintenance of the light is easy to for one person to conduct. The pendant variation of the bu6, with a diameter of 800 mm, includes the series canopy (Ø76 mm) with three parallel suspension cables for connection.



☐ white matt (RAL 9016)
other RAL colors on request



bu6-800-G5

Design: Martin Wallroth

Engineering: mawa design

Wall-mounted, wall-spaced, ceiling-mounted and pendant luminaire, Aluminium housing powder-coated, satined plexiglass 5 mm,

LED module standard: G5:

Downlight: 157 W, Ra > 90 (typ. 92)

Light colour / luminous flux: 2700 K / 21000 lm, 3000 K / 22070 lm,

Uplight: 24 W, Ra > 90 (typ. 92)

Light colour / luminous flux: 2700 K / 2960 lm, 3000 K / 3104 lm,

Life time LED standard:

L80 > 54.000 h (IES LM-80 / TM-21)

bu6-800-G5-4 DALI dim.

bu6-800-G5-7 Leading edge/trailing edge dim.

Mounting possibilities:

Wall and ceiling-mounted (-wm),

Wall connecting plate (-wa) with 3 distances, optionally available with an uplight (-wa-u), standard length 50 mm (other lengths available on request),

Pendant light (-p) incl. canopy, 3 parallel suspension cables and electrical supply optionally available with an uplight (-p-u)





Weight: bu6-800-wm 12 kg,

bu6-800-wa 12,5 kg, bu6-800-p 12 kg


bu6-800-G5-...-wm

bu6-800-G5-...-wa
bu6-800-G5-...-wa-u


bu6-800-G5-...-p
bu6-800-G5-...-p-u



800



800



800

(* standard size)

bullauge 6 Serie bullauge 6 series SYSTEMLEUCHTE SYSTEM LIGHT **bu6-800-G5**

