



wittenberg 4.0 – zoom | wi4-str-fe

STROMSCHIENENSTRAHLER

wittenberg 4.0 – kompakte Bauform, filigranes Gehäuse, größte Gestaltungsvielfalt
Leuchtsérie für anspruchsvolle Beleuchtungsaufgaben und den hochwertigen privaten Bereich



Design: Jan Dinnebier / Engineering: mawa

Produkt- variante	Leistung in W ^{LED}	Abstrahlwinkel in Grad Minimum-Maximum	Dimmungen Matchcode	Lichtfarben und Lichtstrom ^{LED} in Kelvin und Lumen
HighCRI	12,7 W	20° – 50°	-2, -4, -7, -9	2700 K / 930 lm, 3000 K / 980 lm, 4000 K / 1100 lm
d2w	12 W	20° – 50°	-4, -9	1800-3000 K / 1045 lm

(weitere Lichtfarben auf Anfrage)


Matchcode-Kürzel für Dimmungen: -1 schaltbar / -2 Drehpotentiometer am Gehäuse / -4 DALI / -7 Phasenan- und abschnitt / -9 Bluetooth



wittenberg 4.0 – zoom | wi4-str-fe

STROMSCHIENENSTRAHLER

Dimensionen:



Farbe:

- ☐ weiß matt (RAL 9016)
- ☒ schwarz matt (RAL 9005)

Gehäuse:	Aluminium pulverbeschichtet weiß oder schwarz matt (individuelle RAL-Farben auf Anfrage)
Gelenk:	350° dreh- und 90° schwenkbar
Adapter:	Powergear 3-Phasen-Adapter Die Produkte sind für den Einsatz in den Powergear-3-Phasen-Stromschienen PRO-06 und PRO-R6 geeignet.
Abstrahlwinkel:	stufenlos einstellbar von 20° bis 50°
Lichtquelle:	1 × standard-LED (High CRI), Ra > 95 (typ. 98) oder 1 × dim2warm-LED, Ra > 95 (typ. 97)
Lebensdauer:	Standard-LED: L90 (10 k) > 61.000 h (IES LM-80 / TM-21) dim2warm-LED: L80 (10 k) > 50.000 h (IES LM-80 / TM-21)
Betriebsgerät:	inklusive
Betriebsbereich:	AC 220V–240V / 50Hz–60Hz
Zubehör:	(Aktuell ist kein passendes Zubehör verfügbar)
Schutzklasse:	I
Schutzart:	IP20
Gewicht:	730 g

LVK auf mawa-design.de unter Leuchten



wittenberg 4.0 – zoom | wi4-str-fe

TRACK SPOTLIGHT

wittenberg 4.0 – compact dimensions, minimalist design and maximum design versatility
Luminaire series suitable for both high-end private use and sophisticated specialized applications



(illustration exemplary)

Design: Jan Dinnebier / Engineering: Daniel Frey, mawa

Product variants	Performance in W ^{LED}	Beam radiation angle in degrees Minimum-Maximum	Dimming Matchcode	Light colour and luminous flux ^{LED} in Kelvin and Lumen
HighCRI	12,7 W	20 – 50°	-2, -4, -7, -9	2700 K / 930 lm, 3000 K / 980 lm, 4000 K / 1100 lm
d2w	12 W	20 – 50°	-4, -9	1800-3000 K / 1045 lm

(further light colours on request)


Dimming match code abbreviations: -1 switchable / -2 Rotary potentiometer on housing / -4 DALI / -7 Leading edge/trailing edge dimmable / -9 Bluetooth



wittenberg 4.0 – zoom | wi4-str-fe

TRACK SPOTLIGHT

Dimensions:



Colour:

- ☐ white matt (RAL 9016)
- ☐ black matt (RAL 9005)

Housing:	Aluminium housing powder-coated, white or black matt (individual RAL colours on request)
Joint:	Spotlight 350° rotatable and 90° tiltable, joint can be fixable horizontally and vertically on request
Track adapter:	Powergear 3-circuit track adapter Products are suitable for use in Powergear 3-circuit track systems PRO-06 and PRO-R6.
Beam angle:	continuously adjustable from 20° to 50°
Light source:	1 × standard-LED (High CRI), Ra > 95 (typ. 98) or 1 × dim2warm-LED, Ra > 95 (typ. 97)
Life time LED:	Standard-LED: L90 (10 k) > 61.000 h (IES LM-80 / TM-21) dim2warm-LED: L80 (10 k) > 50.000 h (IES LM-80 / TM-21)
Control gear:	included
Operating area:	AC 220V–240V / 50Hz–60Hz
Accessories:	(Currently, no suitable accessories are available.)
Protection class:	I
Degree of protection:	IP20
Weight:	730 g

LDC on mawa-design.de under Lighting